


3108A Paired - RS-485



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

22 awg stranded (7X30) tinned copper, Datalene® insulation, twisted pairs, overall 100% Beldfoil® shield + 90% tinned copper braid, 22 awg stranded TC drain wire, UV resistant PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	3
Total Number of Conductors	6
AWG	22
Stranding	7x30
Conductor Diameter	.030 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FHDPE - Foam High Density Polyethylene

OVERALL CABLING:

Overall Cabling Color Code Chart :

Number	Color
1	White/Blue Stripe & Blue/White Stripe
2	White/Orange Stripe & Orange/White Stripe
3	White/Green Stripe & Green/White Stripe

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	90

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	7x30

3108A Paired - RS-485

Outer Shield Drain Wire Diameter	.030 in.
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.420 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
Non-UL Temperature Rating	60°C
Bulk Cable Weight	85 lbs/1000 ft.
Max. Recommended Pulling Tension	90 lbs.
Min. Bend Radius (Install)	4.25 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM, PLTC OIL RES II
CEC/C(UL) Specification	CM

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
CSA Flame Test	FT1

SUITABILITY:

Sunlight Resistance	Passes UL 1581, 720 Hours
---------------------	---------------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Input/Unfitted Impedance :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Input/Unfitted Impedance (Ohms)
	1			120

Nom. Capacitance Conductor to Conductor @ 1 KHz	11.0 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	20.9 pF/ft
Nominal Velocity of Propagation	78 %
Nom. Conductor DC Resistance of Pair @ 20 Deg. C	14.7 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	1.5 Ohms/1000 ft

Nom. Attenuation (dB/100 ft) :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.5

3108A Paired - RS-485

Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	2.7 Amps per conductor @ 25°C

NOTES:

Notes	Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17
Notes (Cont'd.)	CPE Jacket Optional

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
3108A 0101000	3 PR #22 FHDPE SH PVC	1000	93	BLACK	C D
3108A 0102000	00PR #22 FHDPE SH PVC	2000	184	BLACK	C D

C = CRATE REEL PUT-UP.

D = FINAL PUT-UP LENGTH MAY VARY -0% TO +20% FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 06-08-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.