

1227A1 Paired - DataTwist® 3 UTP Cable



For more information please
call

1-800-Belden1

[See Put-ups and Colors](#)

**Color Code Chart : No. 5 for
Paired Cables (Western
Electric Standard).pdf**

Description:

24 AWG solid bare copper conductors, twisted pairs, polyolefin insulation, PVC jacket. Sequential marking at two foot intervals.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	2
Total Number of Conductors	4
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
---------------------	-----------------

INNER SHIELD:

Inner Shield Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	2	White/Orange Stripe & Orange

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Ripcord	No

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.173 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Bulk Cable Weight	13 lbs/1000 ft.
Max. Recommended Pulling Tension	15 lbs.

1227A1 Paired - DataTwist® 3 UTP Cable

Min. Bend Radius (Install)	0.8 in.
----------------------------	---------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR, UL444
IEEE Specification	802.3 10BaseT, 100BaseT4
TIA/EIA Specification	568-B.2 Category 3
Other Specification	NEMA WC-63 Category 3, UL verified to TIA/EIA-568-B.2, Category 3

FLAME TEST:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	1243A2

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	330 pF/100 m
Nominal Velocity of Propagation	70 %
Nominal Delay	1.5 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	28.0 Ohms/1000 ft
Maximum Conductor DC Resistance @ 20 Deg. C	9.38 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	5 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals :

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. Structural Return Loss (dB)	Fitted Impedance (Ohms)
1	2.56	41.0	No Spec	12.0	100 ± 15%
4	5.58	32.0	No Spec	12.0	100 ± 15%
8	8.50	27.0	No Spec	12.0	100 ± 15%
10	9.71	26.0	No Spec	12.0	100 ± 15%
16	13.10	23.0	No Spec	9.96	100 ± 15%

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1227A1 008U1000	2 PR #24 PP PVC	U1000	13	GRAY	



1227A1 Paired - DataTwist® 3 UTP Cable

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.